



The Barre (UK) Limited
Unit V5, Victoria Mills
WF17 8LL
01274 688 088
info@thebarre.co.uk
www.thebarre.co.uk

The Barre Mirror Range Information Sheet

Delivery & Storage

The mirror range is normally arranged on stillages so that the painted surface of each sheet faces outwards. All sheets are separated with an interleavant powder. The mirror range must be unloaded, stacked upright and fully supported in a safe manner. They should be stood on edge strips of wood, felt or other soft material. We recommend the mirror range is stored in dry well ventilated conditions and not subjected to large temperature fluctuations. Glass should never be exposed to heat or solvents, vapours or chemicals, acid and fuels.

Glass stored in favourable conditions in the original packaging should remain in good condition of up to 6 months.

The mirror range glass is generally delivered in a manner consistent with that of clear glass of similar size and thickness. The glass is marked with a printed identifier on the backing and packing label.

Handling

Care should be taken to ensure the glass is properly fastened and secured to prevent to falling and avoid any damage. Glass should always be handled by staff that have been properly trained and equipped with appropriate handling and safety equipment.

Cleaning & Washing

We recommend the mirror range is washed using warm, demineralised, naturel pH water. Additives such as detergents should not be used in the water. The mirror range should be dried immediately, especially around the edges. Under no circumstances should the product be stacked whilst still wet.

Installation

Great care should be taken when mounting the mirror Range. Contact between the mirror and hard materials such as metal, porcelain and other breakable materials should be avoided. Bushes should be used on drilled glass to avoid contact between the glass fixings. During installation and use, we recommend the mirror is only fitted to flat surfaces and avoid bending the glass out of plane.

* The mirror Range should be installed in compliance with current national regulations and safety standards. For some locations where impact resistant glass is used there may be a requirement to mark the finished cut size to comply with local requirements



The Barre (UK) Limited
Unit V5, Victoria Mills
WF17 8LL
01274 688 088
info@thebarre.co.uk
www.thebarre.co.uk

If bonding, it is the customer's responsibility to ensure that the adhesive is compatible with the backing layer on the mirror. If the adhesive supplier cannot confirm the suitability of their products, we advise that a small test area is tried to verify its long-term compatibility.

We recommend that the adhesive is applied in vertical stripes and that air can circulate between the back of the mirror and the surface to which it is being applied. Pressure should be applied evenly to the mirror surface and supported on blocks until the adhesive has dried. If using adhesive tapes ensure that the adhesive is compatible with the mirror's protective coating and also apply in vertical stripes. We do not recommend the 'closing off' of the bottom edge of the mirror with sealants etc as this could create an area where moisture or water could not drain away. For further information, please consult the GGF Guide for fixing mirrors, which contains good practice and advice for application.

The mirror Range is intended for internal use only. Please note that we do not provide assurance against deterioration of the mirror Range when they are mounted in humid areas such as swimming pools, saunas and gyms.